

GMP FOR SOLAR SYSTEMS

QUALITY

INNOVATION

RELIABILITY



PUMP UP TO 100 PSI

ADJUSTABLE PRV (0-100 PSI)

PUMP CAN RUN DRY

PROVIDE LEAK DETECTION

COMPATIBLE WITH GLYCOL SOLUTIONS (UP TO 50%)

GMP FOR SOLAR SYSTEMS

ITEM #	CAPACITY		ELECTRICAL	PUMP	DISCHARGE CONNECTION	WEIGHT EMPTY		WEIGHT FULL		PRESSURE
	gal	L				lb	kg	lb	kg	
GMP6S	6	22.7	120 Vac/ 60 Hz plug	1.6 GPM 6 L/m	½" FPT	16	7.4	66	30	0-100 psi (0-690 kPa)
GMP18S	18	68.1			½" FPT	25	11.4	175	79.5	0-100 psi (0-690 kPa)

AIR VENT FOR SOLAR SYSTEMS

ITEM #	DESCRIPTION	CONNECT. MNPT	MAX TEMPERATURE	MAX WORKING PRESSURE	DIMENSION DIAM. × HEIGHT		POIDS	
					in	mm	lb	kg
AVHTS	Air vent, brass housing, nickel plated	½"	446°F (230°C)	200 psi	8 × 13	200 × 340	0.6	0.3



Information in this document is founded on the most recent data available at the moment of its publication and is meant for a general presentation of our products. The accuracy of this information cannot be guaranteed. Our products are steadily enhanced and their technical specifications can be modified without prior notice.



If you have any questions, please contact our technical service center at **1 (450) 951.0818** or by email, info@calefactio.com

calefactio.com