

TANKLESS WATER HEATER VALVE

QUALITY

INNOVATION

RELIABILITY

FEATURES AND BENEFITS

- ▶ Secure seal
- ▶ Lead Free
- ▶ Facilitate maintenance with dedicated ports
- ▶ Easy identification of hot and cold valves
- ▶ Provided with 150 PSI pressure relief valve (PRV)

Valve specifications

- ▶ Temperature rating: 40°F to 180°F
- ▶ Body pressure rating: 600 WOG maximum
- ▶ IAPMO listed to NSF/ANSI 61-2010 and IGC 157-2010

PRV SPECIFICATIONS

#Model	PRV075-150	PRV075-30
Set pressure	150 PSI	30 PSI
Temperature rating	99°C	99°C
Maximum heating input:	200 000 BTU	535 000 BTU
Connection	¾" MNPT	¾" MNPT
Certification	CSA ANSI Z21.22	ASME

TANKLESS WATER HEATER VALVE

#Model	Description	Connection
TK075NPT	NPT	¾" FNPT
TK100NPT	NPT	1" FNPT
TK100NPT-30PSI	NPT (with 30 PSI PRV)	1" FNPT
TK075S	Sweat	¾" Sweat
PRV075-150	PRV	¾" MNPT
PRV075-30	PRV	¾" MNPT

NEW!



3/4"



1"



Pressure relief valve (PRV)

Calefactio Solutions Inc.
Quebec (Canada)

T 450 951.0818
F 450 951.2165

calefactio.com
info@calefactio.com

Information in this document is founded on the most recent data available at the moment of its publication and is meant for a general presentation of our products. The accuracy of this information cannot be guaranteed. Our products are steadily enhanced and their technical specifications can be modified without prior notice.