

TANKLESS WATER HEATER VALVE

QUALITY

INNOVATION

RELIABILITY

FEATURES AND BENEFITS

- ▶ Secure seal
- ▶ Lead Free
- ▶ Facilitate maintenance with dedicated ports
- ▶ Easy identification of hot and cold valves
- ▶ Provided with 150 PSI pressure relief valve (PRV)

Valve specifications

- ▶ Temperature rating: 40°F to 180°F
- ▶ Pressure rating: 125 PSI WOG maximum
- ▶ Valve seat rating: 600 WOG
- ▶ IAPMO listed to NSF/ANSI 61-2010 and IGC 157-2010

PRV SPECIFICATIONS

| #Model | PRV075-150 | PRV075-30 |
|------------------------|-----------------|-------------|
| Pressure rating | 150 PSI | 30 PSI |
| Temperature rating | 99°C | 99°C |
| Maximum heating input: | 200 000 BTU | 535 000 BTU |
| Connection | ¾" MNPT | ¾" MNPT |
| Certification | CSA ANSI Z21.22 | ASME |

TANKLESS WATER HEATER VALVE

| #Model | Description | Connection |
|----------------|-----------------------|------------|
| TK075NPT | NPT | ¾" FNPT |
| TK100NPT | NPT | 1" FNPT |
| TK100NPT-30PSI | NPT (with 30 PSI PRV) | 1" FNPT |
| TK075S | Sweat | ¾" Sweat |
| PRV075-150 | PRV | ¾" MNPT |
| PRV075-30 | PRV | ¾" MNPT |

NEW!



3/4"



1"



Pressure relief valve (PRV)

Calefactio Solutions Inc.
Quebec (Canada)

T 450 951.0818
F 450 951.2165

calefactio.com
info@calefactio.com

Information in this document is founded on the most recent data available at the moment of its publication and is meant for a general presentation of our products. The accuracy of this information cannot be guaranteed. Our products are steadily enhanced and their technical specifications can be modified without prior notice.