

HEATING DISTRIBUTION MANIFOLD / CALMAN

The Calman distribution manifold allows the user to connect all the heating zones in a single point. The Calman heat distribution manifold guarantees a uniform temperature of heat carrying liquid in each zone while increasing time and money savings because it is only necessary to install one item rather than a large number of elbows and tees in order to create the required zones.

TECHNICAL SPECIFICATIONS

- ✔ Maximum temperature: 100°C (212°F)
- ✔ Maximum design pressure: 150 PSI
- ✔ Steel frame
- ✔ Drain valve included



Benefits

- ▶ Guarantees a uniform temperature
- ▶ Saves time and money
- ▶ Reduces the number of potential leak points
- ▶ Sufficient space planned to accept pumps between each zone
- ▶ Connects directly to the Calbalance hydraulic separator*

Model#	Connect.	Zones	A		B		C		Weight	
			in	mm	in	mm	in	mm	lb	kg
CM100-3	1"	3	16½	421	18¾	476	6	152.4	3.75	1.7
CM100-4	1"	4	28½	725	18¾	476	6	152.4	4.0	1.8
CM125-4	1¼"	4	28½	725	18¾	476	6	152.4	4.0	1.8
CM125-5	1¼"	5	28½	725	18¾	476	6	152.4	4.4	2.0

*Sold together or individually.

